

More Possibilities.

With Layher Console Brackets.



SpeedyScaf Console Bracket 0.22 m,
WS 19 or 22, with lock against lift-off, without spigot
Ref. No. 1744.019/1744.022
for a deck 19 cm wide



SpeedyScaf Console Bracket 0.36 m
WS 19 or 22, with lock against lift-off
Ref. No. 1745.319/1745.322
for a deck 32 cm wide



SpeedyScaf Console Bracket 0.5 m,
WS 19 or 22
Ref. No. 1744.519/1744.522
For extension or reduction of bay lengths. Furthermore, when using a 0.5 m wide console bracket at a 0.73 m wide scaffold, a platform without any gaps can be built with two decks 61 cm wide.



SpeedyScaf Console Bracket 0.73 m,
WS 19 or 22, reinforced
Ref. No. 1745.719/1745.722
Use with SpeedyScaf in steel without console bracket brace, with SpeedyScaf aluminium with bracket brace



SpeedyScaf Console Bracket 0.73 m, WS 19 or 22
Ref. No. 1744.719/1744.722
for two decks 32 cm wide, or one deck 61 cm wide.



SpeedyScaf section Brace 1.77 m
Ref. No. 1740.177 / 1741.177
for bracing the SpeedyScaf console bracket 0.73 m



Speedy Scaf Console Bracket 0.73 m, WS 19 or 22
Ref. No. 1744.719/1744.722
for two decks 32 cm wide or one deck 61 cm wide.



Console Bracket Brace
Ref. No. 0711.935 / 0711.971
0.73 m cranked, WS 19 or 22
for bracing the SpeedyScaf console bracket 0.73 m



SpeedyScaf Console Bracket 0.73 m,
swiveling
Ref. No. 1744.073
To place upon the frame. After removal of the deck, the console bracket can be swivelled away. Application for corner solutions. Additionally a bracket of 0.73 m can be assembled at the same level.

SpeedyScaf Console Bracket 1.09 m, WS 19 or 22
Ref. No. 1744.119/1744.122
for three decks 32 cm wide, or one each deck 61 cm wide and 32 cm wide.

SpeedyScaf Section Brace 1.95 m, WS 19 or 22
Ref. No. 1740.195/1741.195
for bracing the SpeedyScaf console bracket 1.09 m



Console Bracket for gin wheel 0.73 m
with eyelet for gin wheel
Ref. No. 4417.719/4417.722

D-shackle (for gin wheel)
Ref. No. 4418.000

Gin Wheel
Ref. No. 4419.000
max. loading 50 kg

Gin Wheel with over-run brake,
loading max. 50 kg
Ref. No. 4419.001

Console adapter for gin wheel
Ref. No. 4419.002



Allround Console Bracket 0.28 m
with spigot
Ref. No. 2630.019
for a deck 19 cm wide



Allround Console Bracket 0.39 m
Ref. No. 2630.039
for a deck 32 cm wide



Allround Console Bracket 0.73 m
Ref. No. 2630.073
for two decks 32 cm wide or one deck 61 cm wide, loading max. 2 kN/m² on the bracket

Allround Brace for Console Bracket 2.05 m
Ref. No. 2631.205
for bracing the Allround console bracket 0.73 m

Alum. Allround Brace for Console Bracket 2.05 m
Ref. No. 3209.205
for bracing the Allround console bracket 0.73 m



Allround Console Bracket 1.09 m
Ref. No. 2630.109
for three decks 32 cm wide, or one each deck 61 cm wide and 32 cm wide.
Console brackets must be braced either with an Allround transom at the height of the lower connection of the console bracket or with an Allround diagonal brace 1.09 m x bay height.